



GMP 100.20 - **GMP** 120.20

GMP 100.20 **GMP** 120.20

LIGHT FOOTPRINT FOR YOUR FIRST STEPS INTO INDUSTRIAL IRONING





Chromed Chest.



1 Reduced Utilities Costs

The electronic temperature control system, matched with a newly designed heat distribution system, have drastically cut the electric consumption of GMP 100.20 and GMP 120.20, which feature the lightest footprint in the industry.

2 Chromed Steel Chest

Chromed steel has proven to be the best possible choice for ironing: it ensures an excellent resistance to friction and an extreme longevity.

3 Work Comfortably with Automatic Chest Movement

Work comfortably with GMP 100.20 and GMP 120.20!
With just a light pressure on the foot pedal you can start or stop the roller rotation, as well as open or close the chest to better feed your linen.
Chest movement and roller rotation are controlled by an electric motor.

4 Practical Foot Pedal

Stops the roller rotation and leaves your hands free to accommodate the linen in the feeding process.

5 Electronic Temperature Control The best and most accurate

temperature control system available.
Temperature can be freely adjusted by 1°C to perfectly suit the fabric type processed.

6 User Friendly Control Panel

Large, simple and extremely easy to understand.

7 Aluminium Feeding Table

Feeding your linen has become simpler thanks to the purposely shaped feeding profile.
Aluminium surface can be easily cleaned and will grant the hygiene of your laundry.

8 Low-Cost Maintenance

Simple and reliable construction, matched with the small number of components, will grant the lowest maintenance costs.

GMP 100.20 **GMP** 120.20

TECHNICAL DATA



| | GMP 100.20 | GMP 120.20 |
|--|-------------------------------|-------------------------------|
| Roller dimensions | 1000 x Ø200 mm | 1200 x Ø200 mm |
| Supply tension* | V.230/1/50Hz V.400/3N/50Hz | V.230/1/50Hz V.400/3N/50Hz |
| Heating power | 3,6 kW | 4 kW |
| Motor | 0,18 kW | 0,18 kW |
| Absorption (Amps) | V.230/1: 17A V.400/3: 6A | V.230/1: 19A V.400/3: 7A |
| Ironing speed | 3,3 m/min | 3,3 m/min |
| Hourly production (recommended moisture) | 20kg (15%) | 25 kg (15%) |
| Ironer dimensions (wxdxh) | 1305x420x933 mm | 1505x420x933 mm |
| Packing dimensions (wxdxh) | 1450x550x1120 mm | 1650x550x1120 mm |
| Weight, gross/net | 85,5/74 kg | 93/80,5 kg |

 $^{^*\ \}mathsf{DIFFERENT}\ \mathsf{VOLTAGES}\ \mathsf{THAN}\ \mathsf{INDICATED}\ \mathsf{AVAILABLE}\ \mathsf{ON}\ \mathsf{OPTION}, \mathsf{PLEASE}\ \mathsf{CONTACT}\ \mathsf{OUR}\ \mathsf{SALES}\ \mathsf{OFFICES}$